

SERAGE

QUALITY RELIABILITY VISION

SR5008D



8 CHANNEL DVR



KEY FEATURES

- 8CH Universal
- Recording at up to 4K, 7 fps/ch
- Supports 8+ TVI/AHD/CVI/Analogue + 4 IP – A total of 12 Cameras
- 8CH synchronous playback
- 8CH Audio input, 1CH output
- HDMI, VGA & BNC CVBS output
- IP Recording Bandwidth: 32Mbps ~96Mbps
- Supports IOS & Android, Mobile/Tablets Free Application
- 1 SATA HDD, up to 8TB



NDAA (National Defense Authorization Act) compliant, refers to products that are "safe to use" by government agencies and enterprises.

IP Cam Inputs	24Mbps ~72Mbps Decrease one Analog channel can increase 6Mbps Analog channel and digital channel can be converted
out	72Mbps
Analog video-input	8CH inputs
IP Video Input	4ch, (only IP up to 12ch)
Composite Video Input	Up to 12ch (Analog video + IP video)
Compression	Audio: G.711a Video: H.264/H.265
Display resolution	Analog: 8MP (15fps) 5MP (20fps) 4MP/1080P/720P/960H (30fps) IP: 4K/4MP/1080P/720P Single IP channel preview up to 4K 30 fps
Speed	Main-stream Analog: 8MP:7fps(each ch) 5MP: 12fps(each ch) 4MP: 15fps(each ch) 1080P: PAL:25fps(each ch)/NTSC:30fps(each ch) IP: PAL:25fps(each ch)/NTSC: 30fps(each ch) Sub-stream Max PAL: 704*576:10fps(each ch) NTSC: 704*480:10fps(each ch)"
AI	PID - Perimeter Intrusion Detection LCD - Line Crossing Detection PD&VD - Human&Vehicle Detection"
Event	MD (Sensitivity Level 1~8) Video loss Beep, Email, Push notification to Mobile APP
Playback function	Fast forward / backward (2x, 4x, 8x, 16x) Slow forward (1/2x, 1/4x, 1/8x, 1/16x)
Playback	8MP: 60fps (Max 4CH playback) 5MP: 96fps (Max 8CH playback) 4MP: 120fps (Max 8CH playback) 1080P: 240fps (Max 8CH playback)
Local Web	UI5.0 IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above
Mobile viewer	SERAGE
Push notification	Yes
Password reset	Factory Reset: Press 10 seconds
BNC	1 (704*576)
VGA	1(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
HDMI	1(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 2560*1440, 3840*2160/EDID)
Ethernet	1 RJ45 100/1000 Base-T
USB	USB 2.0*1 (front) USB 3.0*1 + (rear)
Audio	8 in /1 out
HDD	1 SATA HDD, up to 10TB
RS485	1
Alarm Input/out	8 in /1 out
OSD Language	English/French/Spanish/Portuguese/German Italian/Greek/Danish/Finnish/Russia/Hebrew/Turkish Bulgarian/Arabic/Korean/Japanese/Thai/Hindi Romanian/Dutch/Polish
Dimension (WxDxH)	300 X 220 X 53mm
Input Voltage/Current	DC12V/2A
Power consumption (excluding hard disk)	11W
Operating Temperature	-10°C~+50°C (14°F ~ 122°F)
Humidity	Less than 90%RH