

SERAGE

QUALITY RELIABILITY VISION



5MP IP FIXED LENS DOME



KEY FEATURES



SRVDN5FAIB

Imaging Device	1/2.7"
Effective Pixels	5MP 2880 (H) x1620 (V)
Min. Illumination	Color 0.004lux @ F1.6(AGC ON) ; B/W 0 lux @ IR ON
Focal Length (Zoom Ratio)	2.8mm
Max. Aperture Ratio	F No. 1.6
IR Viewable Length	Up to 20m
Wide Dynamic Range	WDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Day & Night	IR cut filter with auto switch (Day/Night/Auto/Image/Schedule)
Privacy Masking	Off/On (4 Zone, Rectangle)
White Balance	Auto/Manual
On-Board Storage	Micro SD slot, up to 256GB
Audio	Built-in microphone
Hardware Reset	Yes
Smart Feature	PID,LCD,PD/VD,SOD,CC,CD,QD, Heat MAP,RSD,LPD,FD (detection)
Video Compression Format	H.265/H.264
Resolution	Mainstream 8MP(3840x2160) 5MP(2592x1944,3072x1728) 4MP(2592x1520),3MP(2304x1296), 1080P(1920x1080), 960P(1280*960), 720P(1280x720) Substream@20fps 720P(1280x720),VGA(640x480), QVGA(320x240) Mobilestream@20fps VGA(640x480), QVGA (320x240)
Bitrate control method	CBR/VBR
Protocol	PD&VD, PID, LCD,CC,SOD,HM,CD,QD LPD,RSD
Application Programming	ONVIF (Profile S/G/T)
Web browser	IE10/11, Safari V12.1 above, Firefox V.52 above, Google chrome V.57 above Edge V.79 abover
Operating Conditions	-35~+60°C/less than ≤ 95% RH
Ingress Protection	IP67
Input Voltage / Current	D12V/POE(IEEE802.3af)
Material	Metal
Weight	556g

WHERE

Ideal for internal use, especially offices, retail stores and restaurants.

WHY

Anti-vandal with no moving parts, stopping people from changing the direction of the camera