




## 16-PORT PoE SWITCH



### KEY FEATURES

#### Network Interfaces

16x10/100M PoE+2x100/1000M Gigabit Ethernet

#### Network Management

Lite Manage (CMS connection ,PoE power consumer statistics, parameter configuration, log checking, firmware update, network topology)

#### IEEE Standard

802.3 802.3u 802.3ab

#### Uplink Rate (Individual Port)

1000M

#### Downlink Rate (Individual Port)

1000M

#### PoE Port

1~16

#### Extension Mode (EPoE)

250 Meters

#### Max. Power (Individual Port)

30W

#### Max. Power (All Ports)

230W

#### Lightning Protection

4KV

### NETWORK

<b>Model</b>	SRPOE16
<b>Interfaces</b>	16x10/100M PoE+2x100/
<b>Network Management</b>	1000M Gigabit Ethernet Lite Manage (CMS connection , PoE power consumer statistics, parameter configuration, log checking, firmware update, network topology)
<b>IEEE Standard</b>	IEEE 802.3\802.3u\802.3ab 802.3x\802.3z\802.3af\802.3at
<b>Uplink Rate (Individual Port)</b>	1000M
<b>Downlink Rate (Individual Port)</b>	1000M
<b>Exchange capacity</b>	7.2Gbps
<b>Packet Forwarding Rate</b>	5.36 Mbps
<b>Internal Cache</b>	2.75Mbits

### POE

<b>PoE standard</b>	IEEE 802.3at/af
<b>PoE Port</b>	1~16
<b>Extension Mode (EPoE)</b>	250 Meters
<b>Max. Power (Individual Port)</b>	30W
<b>Max. Power (All Ports)</b>	230W

### GENERAL

<b>Material</b>	Metal
<b>Weight</b>	2861g
<b>Dimension (WxDxH)</b>	440*221*44mm
<b>Operating Temperature</b>	0°C~+40°C
<b>Operating Humidity</b>	Less than 90%RH
<b>Storage Temperature</b>	-40°C~+85°C
<b>Storage Humidity</b>	Less than 90%RH
<b>Power Specifications</b>	100~240VAC 50/60Hz Max4A 52V/4.8A 250W/G04931(Gospower)
<b>Lightning Protection</b>	4KV