

SERAGE

QUALITY RELIABILITY VISION



TVI MOTIRISED BULLET



SRBT5VFB

Imaging Device	IMX335 1/2.8" Progressive CMOS
Total Pixels	2704 (H) x 2104 (V)
Effective Pixels	2616 (H) x 1964 (V)
Scanning System	progressive scanning
Video Output	BNC
Resolution	5MP 2592 (H) x 1944 (V)
Max, Framerate	5AHD/5TVI: 5MP@20fps 4AHD/4CVI/4TVI:P@25fps N@30fps 2AHD/2CVI/2TVI:P@25fps N@30fps CVBS: 960H "
Focal Length (Zoom Ratio)	2.7-13.5mm
Max. Aperture Ratio	F1.8-3.3
Angular Field of View	H:110.6-32.6°/V:57.3-18.3° D:134.1-37.4°
Min. Object Distance	0.8m~INF(W), 1m~INF(T)
Lens Type	Motorized lens
Audio	N/A
Audio Range	N/A
IR Distance	35
On Screen Display	English
Day & Night	Ext / Color / B/W
Backlight Compensation	Off / User BLC
Wide Dynamic Range	WDR (Off/On) 120db
Digital Noise Reduction	3D DNR
Gain Control	Auto
White Balance	ATW
Electronic Shutter Speed	Auto
Reverse	Mirror
Remote control interface	ACP (AHD Coax Protocol)
Video Transmission Distance	MAX 300M (Cable : 5C 2V)
Operating Temperature	-30°C ~ 55°C / 90%
Ingress Protection	IP66
Input Voltage/Current	12V DC
Power Consumption	IR OFF ≤2W, IR ON ≤6.5W
Color / Material	Metal
Dimension (WxHxD)	TBD
Safety	CE LVD
EMC	CE EMC, FCC
ROHS	RoHS2.0

KEY FEATURES



ZOOM IN



ZOOM OUT

WHERE

Outdoors, especially where the camera needs to be visible for deterrent purposes.

WHY

The motorised lens allows users to zoom in and out for wider or closer view.